



POSIFLEX™
Your Success is Our Vision

State-of-the-Art Scalability in Integrated POS Terminal Solutions

JIVA 5000 SERIES

Highlights

- **15.1" Dual Backlit LCD panel - TFT active matrix**
- **Auto-boot ROM Support (JIVA 5715)**
- **Spill proof water-resistant structure protects circuitry and allows for easy cleaning**
- **A patented finger release lever "geared locking mechanism" easily adjusts the LCD tilt angle from horizontal to vertical**
- **Security lock prevents unauthorized access to input / output data devices**
- **Single Screw design for accessing components and HDD**
- **LED indicates Power "ON"**

Overview

The JIVA 5000 touch terminal series by POSIFLEX offers features such as a software controlled on/off switch to prevent accidental shutdown, optional internal UPS (uninterruptible power supply), and an integrated finger print/MSR (magnetic stripe reader) attachment. The JIVA 5000 series offers two separate configurations.

The JIVA 5700 Thin-Client terminal is designed for applications that require less horsepower on the front-end terminal to run a POS application. The terminal supports Windows CE and XP embedded.

The JIVA 5800 contains a hard disk drive and can be used as a thick-client terminal in a client/server setting and supports Windows 2000/XP Pro.

With a unique space saving footprint design, the JIVA 5700 and 5800 functions for both countertop and wall mount applications. The JIVA 5000 has a solid design that is made to withstand the rigors of daily usage in the harshest environments.



JIVA 5000 Series POS Touch Terminal



JIVA Bundle: JIVA 5815 / 5715, AURA thermal receipt printer, cash drawer, SD-100 attachment with Integrated MSR and finger print sensor or iButton identification

TERMINAL OPTIONS



KP-100 attachment with 40-Dynakey programmable keyboard options: MSR, and finger print sensor

SPECIFICATIONS

	JIVA-5815	JIVA-5715
Max. LCD Resolution	1024 x 768	
Brightness	250 nit	
Audio Line Output	Standard	
LCD Panel	15" TFT	
CPU	C3 1.0 GHz	C3 800 MHz
Memory	DDR 266, SDRAM x 2 DIMM up to 1GB	
Second Display Interfaces	VGA	
Parallel Port	1	
Serial Port	4 available with PS/2 touch interface	
USB Port	2	
CR Port	1 port controls 2 devices (under COM1)	
Mouse Port	1 x PS/2 type	
KB Port	1 x PS/2 type	
CD-ROM Port	1	N/A
LAN Port	10/100 MHz base Ethernet	
FDD	USB Interface	
HDD	20 GB up	N/A
Compact Flash Port	N/A	1 Type II (Compact Flash Memory)
Internal UPS	Yes (Battery Optional)	
ON/OFF Control	Software controlled for Mechanical ON/OFF or Mechanical ON Software OFF	
Touch Sensor	Resistive	
Tilt Adjustment	From 17.5° to 87.5°	
Mounting Option	Table top or wall mount	
Housing Color	Charcoal	
Touch Control Function	Emulate mouse left/right button, double click and drag & drop	
Touch Beep Controls	Sound pitch adjustment sound enable/disable by software	
Power Supply	AC adaptor: Input 100~240V, output DC 12V/60W	AC adaptor: Input 100~240V, output DC 12V/80W
Storage Condition	-20°C ~ +60°C, 10%RH~80%RH; non-condensing, maximum wet bulb 28.9°C	
Operation Condition	0°C ~ +40°C, 20%RH~80%RH; non-condensing, maximum wet bulb 26°C	
Dimension	375mm (W) x 270mm (D) x 360~380mm (H) / 14.8" x 10.6" x 10.8"~15"	
OS Support	WIN 98/2000/XP Pro/ Linux	WIN CE/XP Embedded / Linux thin client
Weight	7.0kg (15.4 lbs.)	7.6kg (17.2 lbs.)
Safety Certifications	PSU: UL/VDE/T mark Terminal: FCC, CE (meet IEC 100-4-2 class A)	



Integrated customer display module mounted on top back side (PD-302)




In a hospitality or kiosk setting, the wall mount bracket is ideal for hanging your JIVA terminal onto the wall thereby regaining precious counter and storage areas



This Space Pole is ideal for retail, hospitality and kiosk applications to accommodate a terminal and its related

JIVA 5700/5800 Main Board Interface Diagram



POSIFLEX™

1280 San Luis Obispo Avenue
Hayward, California 94544 USA

tel : 510-429-7097

fax : 510-475-0982

e-mail : sales@posiflexusa.com

www.posiflexusa.com